

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-20. (canceled)

21. (currently amended): ~~The combination of claim 20, further comprising~~
In combination:

a motor vehicle having a housing, said housing including a first opening
providing access to an interior of said housing;

a spray nozzle body disposed substantially entirely within said interior of said
housing, said spray nozzle body having a bearing axis about which said spray nozzle body is
rotatable, said spray nozzle body further including a spray nozzle outlet aligned with said first
opening;

an adjusting drive manipulator adapted to rotate said spray nozzle body about said
bearing axis, said adjusting drive manipulator including a threaded spindle and a manually
rotatable handwheel, said threaded spindle disposed within said interior of said housing; and

an adjusting element, said adjusting element comprising a grooved abutment on
said spray nozzle body, said threaded spindle engaging said grooved abutment.

22. (currently amended): ~~The combination of claim 20~~ claim 21, wherein said
housing further comprises a receiving element, said spray nozzle body mountable to said
receiving element via a snap-fit engagement.

23. (previously presented): The combination of claim 22, wherein said receiving
element comprises a plurality of snap-lock webs pivotally receiving said spray nozzle body.

24. (currently amended): The combination of ~~claim 20~~ claim 21, wherein said housing further comprises a receiving element, said adjusting drive manipulator mountable to said receiving element via a snap-fit engagement.

25. (previously presented): The combination of claim 24, wherein said receiving element comprises a plurality of snap-lock webs rotatably receiving said adjusting drive manipulator.

26. (currently amended): The combination of ~~claim 20~~ claim 21, wherein said spray nozzle body includes at least one washer fluid input element by which washer fluid may be fed into said spray nozzle body.

27. (currently amended): The combination of ~~claim 20~~ claim 21, wherein said housing comprises a second opening, at least a portion of said manually manually-rotatable handwheel disposed within said second opening and accessible externally of said housing.

28. (canceled)

29. (currently amended): ~~The combination of claim 28, further comprising~~

In combination:

a motor vehicle having a housing;

a spray nozzle body including a pair of pivot pins together defining a bearing axis about which said spray nozzle body is rotatable, said pivot pins rotatably mounted to said housing; and

an adjusting drive manipulator adapted to rotate said spray nozzle body about said bearing axis, said adjusting drive manipulator including a threaded spindle including a manually-rotatable handwheel; and

an adjusting element, said adjusting element comprising a grooved abutment on said spray nozzle body, said threaded spindle engaging said grooved abutment.

30. (currently amended): The combination of ~~claim 28~~ claim 29, wherein said housing further comprises a receiving element, said spray nozzle body mountable to said receiving element via a snap-fit engagement.

31. (previously presented): The combination of claim 30, wherein said receiving element comprises a pair of snap-lock webs respectively receiving said pivot pins of said spray nozzle body.

32. (currently amended): The combination of ~~claim 28~~ claim 29, wherein said housing further comprises a receiving element, said adjusting drive manipulator mountable to said receiving element via a snap-fit engagement.

33. (previously presented): The combination of claim 32, wherein said receiving element comprises a plurality of snap-lock webs rotatably receiving said adjusting drive manipulator.

34. (currently amended): The combination of ~~claim 28~~ claim 29, wherein said spray nozzle body includes at least one washer fluid input element by which washer fluid may be fed into said spray nozzle body.

35. (currently amended): The combination of ~~claim 28~~ claim 29, wherein said housing comprises an opening, at least a portion of said manually manually-rotatable handwheel disposed within said opening and accessible externally of said housing.